



e-MTB TRAIL

PRIME X

Color 1: Matte Graphite / Desert Grey - Color 2: Gloss Black / Frost Green

FRAME	Prime 6061 Xtralite Full Butted Alloy, Forward Geometry, internal removable battery, tapered head tube, Boost 12x148mm rear axle, integrated dropout speed sensor
SIZES	XS: 380mm / S: 390mm / M: 430mm / L: 470mm / XL: 510mm
REAR SHOCK	---
SHOCK SETTINGS	---
FORK	RockShox Recon Silver RL 29, 120mm, Motion control, Solo Air, tapered steerer tube, Boost 15x110mm axle, 42mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload
HEADSET	Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
STEM	MDK Urban 35mm, 6061 forged alloy, 31.8mm barbare
HANDLEBAR	Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 680mm, 9° backsweep, 5° upsweep, 31.8mm barbare
GRIPS	Onoff Shaper
SEATPOST	Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 31.6mm, length 400mm
SADDLE	Fizik Terra Aidon X5 145mm
FRONT BRAKE	Sram Level T, 2 piece caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pad
REAR BRAKE	Sram Level T, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad
BRAKE LEVER	Sram Level T, Direct Link actuation, tooling reach adjust, lever pivot bushings
RIMS	MDK-HP1 29, 30mm internal width, tubeless ready, 32 spokes
SPOKES	CN round stainless steel
FRONT HUB	Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts
REAR HUB	Formula EHL148 Boost 12x148mm, sealed bearings, IS 6 bolts

FRONT TIRE	Maxxis Gritter 29x2.5, single compound, 60TPI, wire bead, tanned wall
REAR TIRE	Maxxis Gritter 29x2.5, single compound, 60TPI, wire bead, tanned wall
CRANKSET	Race Face Aeffect ebike, 165mm
RINGS	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
PEDALS	Sram SX Eagle, 12s, Powerlock
CHAIN	Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1
FRONT DERRAILLEUR	---
REAR DERRAILLEUR	Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click
SHIFT LEVERS	---
CASSETTE	Sram PG-1210, 11-50T, 12s
MOTOR	Bosch Performance Line CX Cruise (25Km/h) GEN4
BATTERY	Bosch Powertube 625Wh
DISPLAY	Bosch Purion
DERRAILLEUR HANGER	Mondraker M068
OTHERS	Front light: 50LUX output DC 6-12V, waterproof Alloy cage. Rear Light: Fender Mount, w/ Reflective, e-bike version, 6-12V. Fenders: Alloy black MDK custom fenders. Rack: Alloy MDK rear Rack, Max loading 25kg. Kickstand: Massload KSA18-40
WEIGHT	---